



LiteDOCK Extreme

EXTRMLD



Voice



Data



SOS



GPS Support



Docking



USB



Charging

BEAM's **LiteDOCK Extreme** is the ideal docking station for using the Iridium Extreme handset for various maritime, transport or fixed site applications.

The Iridium Extreme handset fits securely in the docking station with an easy click to lock mechanism that can be inserted and removed with a press of a button. It is purposely built to allow you to utilize the SOS emergency, with an inbuilt GPS coupling capability that allows you to connect an external GPS antenna to the dock. The Dock also allows you to use the side portable hands-free jack for voice calls.

The Iridium Extreme handset fits securely in the **LiteDOCK**, which features USB data port, phone charging, and integrated Iridium and GPS antenna, making it possible to keep all antenna cables and power permanently connected to the docking station, ready for use.

APPLICATIONS



Luxury Yachts / Boating



Transport



Recreational



In-building

KEY FEATURES

- ▶ **LiteDOCK Extreme CRADLE**
 - Integrated GPS antenna coupling to support External GPS antenna
 - Allows portable hands-free to be connected whilst docked
 - USB data port
 - Integrated Iridium antenna connection
 - 6V DC input, supplied by the auto accessory adaptor of the Extreme
 - Charges Extreme handset
 - Status LED for power indication
 - Supports all Iridium voice & data services
 - Supports hands-free (from the Extreme handset speakerphone only)
 - Easy & convenient installation
 - Universal mounting bracket (RAM)
 - Fully certified - Including ROHS

MyBuddy WEB APPLICATION

MyBuddyExtreme.com is a web based tracking application that can be accessed from any computer via the internet. It features alert, tracking/monitoring and fleet management providing global access to monitor personnel anywhere in the world via the Iridium Extreme handheld phone. MyBuddy's secure web portal, allows access to view high quality global street level maps and satellite imagery to easily pinpoint asset locations and areas of incidence.

MyBuddy supports advanced features such as alert reporting, SMS & Email alerts, track/trace capabilities, automatic asset clustering & automatic map sizing.

Visit: www.mybuddyextreme.com

TECHNICAL SPECIFICATIONS

POWER SPECIFICATIONS

Rated Input	6V DC, 850mA max
AC Power Pack	Not included (Adaptor included with your Iridium Handset)
Average Power Consumption	5 Watts

INTERFACES

Data Port (USB)	USB mini-B 5-pin female (USB Slave).
Power Cable	Inline circular socket to support Iridium 3mm power jack
Iridium Antenna Connector	TNC Female
GPS Antenna Connector	Active 3.3V DC, SMA Female

KIT CONTENTS

Beam LiteDOCK cradle
Universal mounting bracket (RAM)
Earpiece extension cable
Quick Start Guide

ENVIRONMENTAL

Operate Temp. Range*	LiteDOCK -30°C to +70°C Extreme Handset -10°C to +55°C
Charging Temp. Range#	0°C to 45°C
Operating Humidity Range	< 85% RH non-condensing
Storage Temperature	-30°C to +85°C
Weight	Cradle 375g (0.82 lbs)
EMC Compliance	CE
RoHS	Full compliant RoHS Directive EU 2002/95/EC (All 6 substances)
WEEE	For EU countries, this product must be collected separately from household waste, as defined in each region. This product must not be discarded together with household waste.
Flame Retardant	UL94.0
Safety - SELV	AS/NZ 60950-1

* When 9575 Battery is fully charged

Derived from the charging temperature range of the Iridium 9575 handset battery.

ACCESSORIES

RST710	Iridium Mast Mount Antenna
RST714	Iridium Whip Antenna
RST715	Iridium Magnetic Mount
RST720	Iridium Bolt Mount Antenna
RST702	Dual Mode Iridium/GPS Mast Antenna
RST706	Dual Mode Iridium/GPS Whip Antenna

RST705	Dual Mode Iridium/GPS Magnetic Antenna
RST932	Antenna Cable 6m / 18f
RST933	Antenna Cable 12m/36f
RST055A	UPS Battery Pack MyBuddy Extreme

APPROVED BEAM RESELLER

www.beamcommunications.com

www.beamcommunications.com

EXTRMLD_REV01_11/11

AFRICA

ASIA

AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA